



REV.	ECN NO.	LOCATIONS	DESCRIPTION	DATE	DESIGN
A0			Initial	2012/12/11	Jamie Zie



1. 特性:

- 额定电压 : 250V
 额定电流 : 3AMP
 接触阻抗 : 30mΩ MAX.
 绝缘阻抗 : 1000MΩ MIN. at 500V DC
 耐电压值 : 500V AC RMS for 1Minute
 温度范围 : -55°C ~ 105°C
2. 材料:
- 塑胶 : PBT+30% G, F (UL94V-0) 藍綠色
 端子 : H62 (C2800) 铜 镀镍底50U", 表面镀锡80U",
 焊接部位镀金G/F.
 鱼叉 : H62 (C2800) 铜 镀镍底50U", 表面镀锡80U",
 外壳 : SPCC 表面镀镍 50U"
 螺丝 : SPCC 表面镀镍 50U"

NO	VARIETY	QTY	MATERIAL	REMARK
 Matrix Electronics Co.,Ltd				
TOLERANCE: X. ±0.38 X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 ANGLE: ±3°		DESIGN BY : Jamie Zie	DATE : 2012/12/11	PART NAME: DSUB 9M+9M Blue-green
		CHECKED BY: Vilen Lee	DATE : 2012/12/11	PART NO. MDS18-00-03
 UNIT: mm [inch]		APPROVED BY1: Richard Hsieh	DATE : 2012/12/11	MOLD NO. NA
		APPROVED BY2: Richard Hsieh	DATE : 2012/12/11	DRAW NO.
SCALE:1:1	SIZE:A4		SHEET NO. 1	1 □ 1