

GP Component

REV.	ECN NO.	LOCATIONS	DESCRIPTION	DATE	DESIGN
A0			Initial	2014/09/25	Phebe Su

600±20

接点表

P1		P2	P1		P2
1	黑+	5	6	对绞白	3
12	同轴(黄+绿+棕+橙)中的编织	8	7	对绞绿	2
13			2	同轴黄	10
24			3	同轴绿	9
4		1	23	同轴棕	7
9	红		22	同轴橙	6
16			铁壳	编织	铁壳
21					

材料:

1. 线材: (30AWG coax*1C)*4+(30AWG*1P+AL/MY)+24AWG*2C+AL+B(16/4/0.12)

OD:4.8mm 外被颜色:黑色.

2. 连接器:USB 3.1 Micro B公 黑胶芯 端子漂金, 焊线式

3. 连接器:USB 3.1 C公 端子漂金, 铜壳镀镍, 焊线式+PCB板

4. 透明PE料.

5. 外模料:PVC 45P, 颜色:黑色.

测试条件:

1. 100% 短路&断路&错位测试.

2. 绝缘阻抗:2M ohm(MIN)

3. 导通阻抗:5 ohm(MAX).

4. 耐压测试:DC 300V/10ms

NO	VARIETY	QTY	METERIAL	REMARK
 Matrix Electronics Co.,Ltd				
TOLERANCE: X:X ±0.38 X:XX ±0.25 X:XXX ±0.13 ANGLE: ±3°		DESIGN BY : Phebe Su	DATE : 2014/09/25	PART NAME: USB 3.1 CM TO MICRO USB 3.1 BM
CHECKED BY: Vicky Hsieh		DATE : 2014/09/25	PART NO.	MCABLE-UTU-017-RS
APPROVED BY1: Richard Hsieh		DATE : 2014/09/25	MOLD NO.	NA
APPROVED BY2: Richard Hsieh		DATE : 2014/09/25	DRAW NO.	
SCALE:1:1 SIZE:A4			SHEET NO.	1 OF 1