







GP Component

REV.	ECN NO.	LOCATIONS	DESCRIPTION	DATE	DESIGN
AO			Initial	2017/07/28	Phebe Su



NOTES:

1.MATERIAL:

MOLDING: LCP BLACK UL94 V-0

CONTACT: COPPER ALLOY.

GOLD FLASH PLATED Min ON CONTACT AREA,
100u" Min TIN (LEAD FREE) ON SOLDER AREA,

SHELL: SUS304-H,T=0.30±0.03mm

50u" NICKEL PLATING OVER ALL.

SHILD: SUS304-H,T=0.12±0.03mm

2.MECHANICAL:

INSERTION: 5~20N.

EXTRACTION: 8~20N AFTER TEST.

DURABILITY: 10000 CYCLES

3.ELECTRICAL:

CURRENT: 5A FOR VBUS;

1.25A FOR GND PIN.

0.25A FOR OTHER.

VOLTAGE: 20 V MAX

WITHSTANDING VOLTAGE: 100V AC R.M.S.

CONTACT RESISTANCE: 40mΩ MAX.

INSULATION RESISTANCE: 100MΩ MIN.

4.ENVIRONMENTAL

TEMPERATURE RANGE -40°C ~ +85°C

MATRIX PART NO:

MUSB12-01-262

MATRIX USB

Series number

Pin Number

Plating
01:Gold Flash
15:15u"
30:30u"


USB TYPE-C FULL-FEATURED RECEPTACLE INTERFACE PIN ASSIGNMENTS

PIN	Signal Name	Description	PIN	Signal Name	Description
A1	GND	Ground return	B12	GND	Ground return
A2	SSTxp1	Positive half of first SuperSpeed TX differential pair	B11	SSRXp1	Positive half of first SuperSpeed RX differential pair
A3	SSTxn1	Negative half of first SuperSpeed TX differential pair	B10	SSRXn1	Negative half of first SuperSpeed RX differential pair
A4	Vbus	Bus Power	B9	Vbus	Bus Power
A5	CC1	Configuration Channel	B8	SBU2	Sideband Use (SBU)
A6	Dp1	Positive half of the USB 2.0 differential pair-Position 1	B7	Dn2	Negative half of the USB 2.0 differential pair-Position 2
A7	Dn1	Negative half of the USB 2.0 differential pair-Position 1	B6	Dp2	Positive half of the USB 2.0 differential pair-Position 2
A8	SBU1	Sideband Use (SBU)	B5	CC2	Configuration Channel
A9	Vbus	Bus Power	B4	Vbus	Bus Power
A10	SSRXn2	Negative half of second SuperSpeed RX differential pair	B3	SSTxn2	Negative half of second SuperSpeed TX differential pair
A11	SSRXp2	Positive half of second SuperSpeed RX differential pair	B2	SSTxp2	Positive half of second SuperSpeed TX differential pair
A12	GND	Ground return	B1	GND	Ground return



Matrix Electronics Co.,Ltd

TOLERANCE:

X.X ±0.25
X.XX ±0.15
X.XXX ±0.05
ANGLE: ±3°

UNIT: mm [inch]

SCALE:1:1 SIZE:A4

DESIGN BY :

Phebe Su

CHECKED BY:

Vicky Hsieh

APPROVED BY1:

Richard Hsieh

APPROVED BY2:

Richard Hsieh

DATE :

2017/07/28

DATE :

2017/07/28

DATE :

2017/07/28

DATE :

2017/07/28

PART NAME:

USB 3.1 Type C Gen 2 Male

Vertical, 11:10H

PART NO.

MUSB12-01-262

MOLD NO.

NA

DRAW NO.

SHEET NO.

1 OF 1