


A horizontal number line with tick marks labeled 1 through 7. The line is divided into six equal segments by the tick marks.

CR Component	REV.	ECN NO.	LOCATIONS	DESCRIPTION	DATE	DESIGN
--------------	------	---------	-----------	-------------	------	--------



A horizontal number line with tick marks labeled 1 through 7. The line is divided into six equal segments by the tick marks.

1.MATERIAL:

MOLDING: LCP BLACK UL94 V-0

CONTACT: COPPER ALLOY.

GOLD FLASH PLATED Min ON CONTACT AREA,

SHELL: SUS304-H,T=0.30±0.03mm

50u" NICKEL PLATING OVER ALL.

SHILD:SUS304-H,T=0.12±0.03mm

.MECHANICAL:

INSERTION: 5~20N.

EXTRACTION: 8~20N AFTER TEST.

DURABILITY: 10000 CYCLES

.ELECTRICAL:

CURRENT: 5A FOR VBUS;

1.25A FOR GND PIN.

0.25A FOR OTHER.

20 V MAX

WITHSTANDING VOLTAGE: 100V AC R.M.S.

CONTACT RESISTANCE: 40mΩ MAX.

INSULATION RESISTANCE: 100MΩ MIN.

ENVIRONMENTAL

TEMPERATURE RANGE $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$

MUSR13_01_347

Series number

Dis. Neurolog.

01:Gold Flash

15:15u''

Co.,Ltd



SESSION ID	DATE	PART NAME
------------	------	-----------

TOLERANCE:		DESIGN BY :	DATE :	PART NAME:	
X.X	±0.25	Phebe Su	2017/07/28	USB 2.0 Type C Female	
X.XX	±0.15	CHECKED BY:	DATE :	R/A, CL 1.68	
X.XXX	±0.05	Vicky Hsieh	2017/07/28	PART NO.	MUSB12-01-247
ANGLE: ±3°		APPROVED BY1:	DATE :	MOLD NO.	NA
		Richard Hsieh	2017/07/28		
UNIT: mm [inch]		APPROVED BY2:	DATE :	DRAW NO.	
SCALE:1:1	SIZE:A4	Richard Hsieh	2017/07/28	SHEET NO.	1 OF 1