





GP Component

REV.	ECN NO.	LOCATIONS	DESCRIPTION	DATE	DESIGN
A0			Initial	2016/03/15	Phebe Su
A1			新增備註	2021/01/06	Hanson



- NOTES:
- MATERIAL:
HOUSING:PA46,UL94V-0,BLACK
CONTACT:PHOSPHOR BORNZE,T=0.35
SHELL:COPPER ALLOY
 - FINISH:
CONTACT:GOLD 3u" ON CONTACT AREA
MATTE TIN PLATING ON SOLDER TAIL
SHELL:NICKEL PLATING OVERALL
 - OPERATING TEMPERATURE:-40°C~+85°C.
 - JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F



ORDER INFORMATION :

MRJ N - 28 T 449 T RS


Matrix-RJ45

F : 10/100
G : 10/100/1000
N : Pure Connector

RS: ROHS
HF: Halogen Free
Industrial temperature
Series Number

S: SMD
T: THT

11:1X1 ; 21:2X1
12:1X2 ; 22:2X2
14:1X4 ; 24:2X4
16:1X6 ; 26:2X6
18:1X8 ; 28:2X8
1U:RJ+USB



RECOMMENED PCB LAYOUT
COMPONENT SIDE
TOLERANCE ±0.05

△ 備註	
1	LED燈罩高度低於≤0.5mm
2	LED燈罩不可下陷(低於外殼)

Matrix Electronics Co.,Ltd

TOLERANCE: X.X: ±0.3mm X.XX: ±0.25mm X.XXX: ±0.15mm ANGLE: ±3°	DESIGN BY : Hanson Huang	DATE : 2021/01/06	PART NAME: RJ45 CONNECTOR 2X8 PORT W/LED, 6PBC, Shielded, Thru-Hole
UNIT: mm [inch]	CHECKED BY: Vicky Hsieh	DATE : 2021/01/06	PART NO. MRJN-28T449TRS
SCALE:1:1 SIZE:A4	APPROVED BY1: Richard Hsieh	DATE : 2021/01/06	MOLD NO. NA
	APPROVED BY2: Richard Hsieh	DATE : 2021/01/06	DRAW NO. NA
			SHEET NO. 1 OF 1