



NOTES:

- MATERIAL: HOUSING-->PBT+30%GF(P/N: 4020303718),COLOR: BLACK, UL94V-0 COMPLIANCE.
 材質:PBT+30%GF,顏色:黑,符合UL94V0
 TERMINAL 1, P/N: 3354388900M, TERMINAL 2, P/N: 3354445500M
 TERMINAL 3, P/N: 3354389100M, TERMINAL 4, P/N: 3354445400M
- MATERIAL MUST BE APPROVED BY DELTA.
 材料須被台達認證。
- MUST MEET DELTA'S SPEC:10000-0007,10000-0131,10000-2008.
 必須符合台達規範10000-0007,10000-0131,10000-2008.
- ANY FEATURE NOT MARKED HERE SHOULD FOLLOW 3D MODEL AND SATISFY TOLERANCE LIST.
 任何未標註之尺寸依照3D 檔案且符合公差表。
- THE SYMBOL "Ⓢ" DENOTE IMPORTANT DIMENSION, MUST BE CAREFUL IN INSPECTION CONTROL.
 01~06: INSPECT EVERY LOT BEFORE PRODUCTION AND IMPLEMENT SPC & MSA.
 07~19: INSPECT EVERY LOT BEFORE PRODUCTION.
 標註"Ⓢ"為重要尺寸,必須仔細查檢管控。
- MIN. OPERATING TEMPERATURE: -40°C
 MAX. OPERATING TEMPERATURE: 85°C
- CONTACT PLATING: TERMINAL 1 & 2 & 3 & 4: SILVER PLATED
- RATED AC/DC CURRENT (MAX.): 40A; RATED AC/DC VOLTAGE (MAX.): 52V
- ONLY FOR AUTOMOTIVE.
 車規專用。

* 除本份規格文件另有規定外,未得到台達之事前書面同意,供應商不得擅自變更其所交付予台達所有產品之原料來源、材質、生產製程及任何已載於產品說明書(或規格承認書)之規格。
 * Unless otherwise specified in this document, a written approval from Delta in advance is required for supplier before making change that includes material, source of supply, manufacturing process and all characteristics list in product specification or any approval specification.

台達電子工業股份有限公司 DELTA ELECTRONICS, INC.		Drawn: 黃柏璋 POWEL HUANG 11/21'24	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF APPARATUS OR DEVICES WITHOUT PERMISSION.		DESCRIPTION: CONNECTOR HEADER	
DIMENSIONAL TOLERANCES () () () () <30 :±0.25 DECIMALS () UP-100 :±0.2 250-300 :±0.4 UP-600 :±1.5 >30-100 :±0.35 X :±0.30 100-150 :±0.25 300-350 :±0.45 600-900 :±2.4 >100-300 :±0.5 X.X :±0.20 150-200 :±0.3 350-400 :±0.5 900-OVER :±3.1 ABOVE 300 :±0.6 X.XX:±0.10 200-250 :±0.35		PART NO.: 3073902400M	
SCALE 2:1 UNIT mm USED ON AUTOMOTIVE FAN		SHEET 2 OF 2	